555/1, Energy Complex, Building A, 15th Floor, Vibhavadi Rangsit Rd., Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8125

บริษัท จีชี สไตรีนิคส์ จำกัด

555/1 ศูนย์เอนเนอร์ยีคอมเพล็กซ์ อาคารเอ ขั้น 15 ถนนวิภาวดีรังสิด แขวงจคุจักร เขดจตุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร +66-2265-8125



Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name DIAREX GPPS In Case of Thailand:

> **Emergency and** +66(0)-3897-6682 **Technical** +66(0)-3897-6683 Information +66(0)-3897-6684

06/08/2019 **Revision Date Synonym** General Purpose Polystyrene, Vinylbenzene

polymer, Styrene polymer

Ethenylbenzene homopolymer **Print Date** 06/08/2019

Chemical **Family**

Product THF77, THH102, THH103 **Revision No.** 06

Grade

PS0001 (EN) SDS No. 9003-53-6 **CAS Registry**

Number

GC Styrenics Company Limited Company

7, I-1 Road, Maptaput Industrial Estate, Map Ta Phut, Name / Muang Rayong District, Rayong 21150, Thailand,

Address

Section 2. Hazards Identification

Emergency Overview Irritating vapors to respiratory system and eyes may form when polymer is processed at high

temperatures.

Molten or heated material in skin contact can cause severe burns.

Routes of Entry FOR HOT MATERIAL: Skin contact. Eye contact. Inhalation.

Eyes

Potential Acute Health Effects

Heated Polymer: Eye contact can cause serious thermal burns. Vapors formed when

polymer is heated may be irritating to the eye.

Dust may cause mechanical irritation to eye.

No known acute effects of this product resulting from skin contact at room temperature. Skin

Heated Polymer: skin contact can cause serious thermal burns.

Negligible at room temperature. Nuisance dusts can be irritating to the upper respiratory

tract.Irritating vapors may form when the polymer is processed at high temperatures. Ingestion No effects are expected for ingestion of small amounts. May be a choking hazard.

Potential Chronic Health CARCINOGENIC EFFECTS: Polystyrene is not a known carcinogen.

Effects Not listed as a carcinogen by OSHA, NTP or IARC.

Medical Conditions Pre-existing disorders involving any target organs mentioned in this SDS as being at Aggravated by risk may be aggravated by over-exposure to this product.

Overexposure

Overexposure/Signs/ No adverse health effects anticipated from the solid pellet.

Symptoms

GC Styrenics Co., Ltd.

555/1, Energy Complex, Building A, 15th Floor, Vibhavadi Rangsit Rd., Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8125



บริษัท จีซี สไตรีนิคส์ จำกัด

555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 15 ถนนวิภาวดีรังสิต แขวงจตุจักร เขตจตุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร+66-2265-8125

Section 3. Composition and Information on Ingredients

% by Weight Substance Name CAS No. Polystyrene 9003-53-6 > 96.75

Section 4. First Aid Measures

Rinse with water for a few minutes. Seek medical attention if necessary **Eve Contact**

Polymer: NO known EFFECT on skin contact, rinse with water for few minutes. **Skin Contact**

Heated Polymer: For serious burns from heated polymer, get medical attention. In case of skin contact, immediately immerse in or flush with clean, cold water.

Inhalation Non-toxic material. Dusts in high concentrations may cause irritation to upper respiratory tract.

Allow the victim to rest in a well-ventilated area.

Not expected that the ingestion of this material causes an effect on health. The toxicity of a **Ingestion**

single oral dose in considered. extremely low.

Section 5. Fire Fighting Measures

May be combustible at high temperature. Flammability of the Product

488 - 496 ° C. **Auto-ignition**

Temperature

>550 °C. **Flash Points**

296 - 360°C (under condition of decomposition excess heating decompose polystyrene and

decomposed materials makes flash point lower.

Flammable Limits Not available.

Can produce carbon monoxide (CO), carbon dioxides (CO2), styrene, aliphatic **Products of Combustion**

hydrocarbons and soot.

Fire Hazards in Presence of

Various Substances

No specific information is available in our database regarding the flammability of this

product in presence of various materials.

SMALL FIRE: Dry chemical extinguisher (ABC or AB). Use water spray or fog. Fire Fighting Media and

Instructions

LARGE FIRE: Use water spray or fog. Do not use water jet.

May re-ignite itself after fire is extinguished

Protective Clothing (Fire) Wear MSHA/NIOSH-approved self-contained breathing apparatus or equivalent

and full protective gear.

Special Remarks on Fire

Hazards

Fire may produce irritating gases and dense smoke.

Flowing material may produce static discharge, igniting dust accumulations.

Special Remarks on

Explosion Hazards

Processing or material handling equipment may generate dust of sufficiently small particle size, that when suspended in air may be explosive.

555/1, Energy Complex, Building A, 15th Floor, Vibhavadi Rangsit Rd., Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8125

บริษัท จีชี สไตรีนิคส์ จำกัด

555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 15 ถนนวิภาวดีรังสิด แขวงจดุจักร เขตจดุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร +66-2265-8125



Section 6. Accidental Release Measures

Small Spill and Leak Pellets on the floor could present a serious slipping problem. Good housekeeping must

be maintained at all times to avoid this hazard. Sweep, shovel, or vacuum material into

clean containers.

Large Spill and Leak Use a shovel to put the material into a convenient waste disposal container. Do not allow

any potentially contaminated water with pellets to enter any waterway, sewer or drain.

Section 7. Handling and Storage

Handling Avoid Temperatures of 600°F (316°C) or above.

Handling of plastic may form nuisance dust. Protect personnel.

Pneumatic material handling and processing equipment may generate dust of sufficiently small particle size that, when suspended in air, may be explosive. Dust accumulations should be controlled through a comprehensive dust control program that includes, but is not limited to, source capture, inspection and repair of leaking equipment, routine housekeeping and employee training in hazards. See NFPA 654.

Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

When handled in bulk quantities, this product and its associated packaging may present a crushing hazard due to the large masses involved, possibly resulting in severe injury or

death.

Keep container dry. Keep in a cool place. Ground all equipment containing material. Keep container tightly closed. Keep in a cool, well-ventilated place. Combustible materials

should be stored away from extreme heat and away from strong oxidizing agents.

Section 8. Exposure Controls/Personal Protection

Control Parameter Occupational Exposure limit (OEL)

Exposure limit value GESTIS-International limit values for chemical agents

airborne levels below established levels. If user operations generate dust, fumes or mist, use

ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection

Storage

Eyes Safety glasses with side shields.

Body Coveralls.

Respiratory Ventilation is normally required when handling this product at high temperatures. Wear

appropriate respirator when ventilation is inadequate.

Hands Thermally insulated gloves required when handling hot material.

Feet Shoes.

Protective Clothing (Pictograms)



Personal Protection in Case of a Large Spill

Safety glasses. Gloves.

GC Styrenics Co., Ltd.

555/1, Energy Complex, Building A, 15th Floor, Vibhavadi Rangsit Rd., Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8125



555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 15 ถนนวิภาวดีรังสิต แขวงจตุจักร เขตจตุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร+66-2265-8125



Product Name

Flash Point

Exposure Limits

Polystyrene (Impact)

Not established.

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

9.1. General Information (appearance, odor)

Physical State and Appearance Solid. Pellets. Color Creamy white Odor Odorless. **Oder Threshold** Not available. 9.2. Important Health, Safety and Environmental Information

296 - 360°C (under condition of decomposition excess heating decompose

polystyrene and decomposed materials makes flash point lower.

Not applicable. Flammability (solid,gas)

Flammable Limited in Air Lower; Not applicable.

Upper; Not applicable

>550 °C.

Auto ignition Temperature 488 - 496 °C. Vapor Pressure Not applicable.

Boiling Point (760 mmHg) Not applicable.

VOC 0 (%)

Solubility Insoluble in water. Soluble in esters, ketone, aromatic hydrocarbons.

Volatility

Decomposition Temperature Equilibrium point between polymerization and de-polymerization is around 250 °C.

9.3. Other data Molecular Weight Not applicable. Molecular Formula (-CH(C6H5)-CH2-)x

Melting Point > 132 °C **Specific Gravity** 1.04 (Water = 1)Freezing Point Not applicable

Section 10. Stability and Reactivity

Reactivity No information available.

Stability This product is stable under normal conditions.

Hazardous Under normal conditions of storage and use, hazardous polymerization will not occur

Polymerization

Conditions to Avoid Keep away from heat , flames and sparks. Avoid Temperatures of 600°F (316°C) or above. Incompatibility with

Various Substances

Reactive with strong oxidizing agents.

Hazardous Decomposition Products

Hazardous decomposition products are carbon monoxide, carbon dioxide, dense smoke, and various hydrocarbons. Exposure of polystyrene to extremely high temperatures (600 deg F or higher) may cause partial decomposition. Chemicals that may be released include styrene monomer, benzene,

and other hydrocarbons.

GC Styrenics Co., Ltd.

555/1, Energy Complex, Building A, 15th Floor, Vibhavadi Rangsit Rd., Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8125

555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 15 ถนนวิภาวดีรังสิต แขวงจตุจักร เขตจตุจักร กรุงเทพฯ 10900

บริษัท จีซี สไตรีนิคส์ จำกัด

โทร+66-2265-8400 โทรสาร+66-2265-8125



Section 11. Toxicological Information

Acute Toxicity

Ingestion Single dose oral LD50 has not been determined. Typical for this family of materials, estimated.

LD50,Rat > 5,000 mg/kg

Dermal The dermal LD50 has not been determined. Typical for this family of materials, estimated.

LD50,Rabbit > 2,000 mg/kg.

Inhalation The LD50 has not been determined.

Eye damage / Irritation Solid or dust may cause irritation or corneal injury due to mechanical action. Elevated

temperature may generate vapor levels sufficient to cause eye irritation. Effects may

include discomfort and redness.

Skin corrosion / irritation Prolonged contact is essentially nonirritating to skin. Mechanical injury only. Under normal

processing conditions, material is heated to elevated temperatures, contact with the material may

cause thermal burns.

Sensitization

Skin No relevant information found.

Respiratory No relevant information found.

Repeated Dose Toxicity Additives are encapsulated in the product and are not expected to be released under normal

Processing conditions or foreseeable emergency.

Chronic Toxicity and Carcinogenicity

No relevant information found.

Development Toxicity No Reproductive Toxicity No

No relevant information found. No relevant information found.

Section 12. Ecological Information

Ecotoxicity This product is essentially a high molecular weight polymer , not regarded as ecotoxic .

Persistence and degradability

This product is not readily biodegradable. Persistent in the environment.

Bioaccumulation May accumulate in soil and water systems.

Fire Hazards in Presence of Various Substances

No specific information is available in our database regarding the flammability of this product

in presence of various materials.

Explosion Hazards in Presence of Various Substances

Risks of explosion of the product in presence of mechanical impact: Not expected. Risks of

explosion of the product in presence of static discharge: Possible.

Risk of explosion from dust accumulation of this product is possible. See MSDS section 7

Handling for more information.

GC Styrenics Co., Ltd.

555/1, Energy Complex, Building A, 15th Floor, Vibhavadi Rangsit Rd., Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8125



555/1 ศูนย์เอนเนอร์ยีคอมเพล็กซ์ อาคารเอ ขั้น 15 ถนนวิภาวดีรังสิด แขวงจคุจักร เขดจตุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร +66-2265-8125



Section 13. Disposal Considerations

Description and handling

Of residues

Appropriate methods of Disposal of preparation

Incineration

Recycling

Landfilling **National and Community** provisions relating Waste Information

Consult your local or regional authorities.

The same safety consideration apply to scrups / waste as apply to the preparation.

Residues should be disposed of as required by national and local regulations.

Must be done under approved conditions, possibly with energy recovery and only at suitable facilities equipped with a scrubber for the treatment of fumes before their release into the atmosphere.

After suitable treatment (cleaning, grinding, etc.), the preparation can be safety re-used, as is or mixed with fresh material, when this is compatible with the intended final application.

Should be avoided as far as possible. If unavoidable, use approved landfill sites.

Directive 91/156/EEC of 18 March 1991; Directive 91/189/EEC of 12 December 1991; Directive

91/62/EEC of 20 December 1994.

Transfer to an approved disposal area in accordance with federal, state, and local regulations.

Section 14. Transport Information

IMDG

Proper Shipping Name Not regulated. **Hazard class** Not regulated. Not regulated. **UN Number Packing Group** Not regulated.

Special Provisions None.

Marine Pollutant Not applicable

Environmental hazard

Proper Shipping Name Not regulated Not regulated **Hazard class** Not regulated **UN Number** Not regulated **Packing Group**

Special Provisions None

Environmental hazard Not applicable

ADR

Proper Shipping Name Not regulated **Hazard class** Not regulated Not regulated **UN Number Packing Group** Not regulated

Special Provisions None

Environmental hazard Not applicable

GC Styrenics Co., Ltd.

555/1, Energy Complex, Building A, 15th Floor, Vibhavadi Rangsit Rd., Chatuchak, Bangkok 10900 TEL+66-2265-8400 Fax +66-2265-8125



555/1 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาคารเอ ชั้น 15 ถนนวิภาวดีรังสิต แขวงจดุจักร เขตจดุจักร กรุงเทพฯ 10900 โทร+66-2265-8400 โทรสาร+66-2265-8125



Section 15. Regulatory Information

Thailand : Hazardous Substance Act, B.E. 2535

This product does not contain substances listed in Thai Hazardous substances Act.

Thailand: Notification of Ministry of Interior (Occupational Health and Safety in Chemical) All components of this product are not listed.

HCS Classification

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

International Regulations DSCL (EEC)

This product is not classified according to EU legislation

International List

Australia inventory (AICS): This material is listed or exempted.
China inventory (IECSC): This material is listed or exempted.
Japan inventory (ENCS): This material is listed or exempted.
Japan inventory (ISHL): Not determined.
Korea inventory (KECI): This material is listed or exempted.

DISCLAIMER

- This Applications specified herein is for reference only and not suitable for using in the manufacturing of any products in medical and pharmaceutical sectors.
- Determination of suitability of the product for the use and purpose shall be the customer's responsibility. Customer is obligated to inspect and test the product for such suitability. Customer is responsible for appropriate, safe, legal use processing and handling of the product.
- To our best knowledge, information contained herein is true and accurate as of the date of its publication. However, we make no representations or warranties with respect to accuracy, reliability and completeness of the information contained herein for any purpose.
- No warranties, express or implied, which extend beyond the description herein are given by us. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose.
- We assume no liability for any use of the product in combination with other materials. The information contained herein entirely relates to the product when it is not used in combination with any third party's materials.

Section 16. Other Information

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact.